



GPS/GSM Terminal

FM3200

- Car security/tracking
- Parametrized operation (acquire & send)
- ALARM button
- Online tracking
- Geo-fence
- Motion sensor
- Low energy consumption in sleep mode
- Internal backup battery

FM3200 is light terminal with GPS and GSM connectivity, which is able to get device coordinates and other data and transfer them via GSM network. This device is perfectly suitable for applications where location acquirement of remote objects is needed. So you can track your remote objects (trucks, cars, ships etc) quickly and easily.

FM3200 can perform tasks on remote objects, such as monitoring engine status, controlling truck's door and etc.

In case of loosing connection FM3200 can store up to 15000 records, and once the connection is established the device will send stored data via GPRS. So you won't lose your data (coordinates, sensors data and etc.).



TECHNICAL DETAILS

GSM

- Dual-Band 900/1800 MHz
- GPRS class 10 (up to 85,6 kbps)
- SMS (text/data)

GPS

- NMEA, GGA, GGL, GSA, GSV, RMC, WGS-84 protocol compatible
- 50 channel GPS receiver
- -160dBm sensitivity

Interface

- Inputs:
 - 2 digital inputs(for door opening monitoring, panic button or other digital sensors)
 - 2 pins for power supply can measure vehicle battery voltage (analog) and (in most cases) engine start (generated higher voltage on vehicle's battery)
 - ♦ Virtual (Data) inputs:
 - + Driven distance (GPS odometer)
 - + Vehicle speed monitoring
- 2 Digital Outputs
- Power supply +10V...+30V
- 3 Status LEDs
- USB Port
- Configuration and firmware upload
- Internal GSM antenna
- External GPS antenna

FEATURES

- GPS and I/O data acquisition
- Real Time tracking
- Smart algorithm of data acquisition (time, distance and event based)
- Sending acquired data via GPRS (TCP/IP and UDP/IP protocols)
- Smart algorithm of GPRS connections (GPRS traffic saving)
- Operating in roaming networks (preferred GSM providers list)
- Events on I/O detection and sending via GPRS or SMS.
- Scheduled 24 coordinates SMS sending
- 5 geofence zones (rectangular or circle)
- Sleep mode (saving vehicle's accumulators)
- Internal NiMh 300 mAh backup rechargeable battery
- OTA (firmware updating via GPRS)
- Motion sensor
- Small and easy to mount case



Applications

- Security
- Track and trace
- Road assitance
- Toll collect
- Insurance

HQ JSC Teltonika

Saltoniskiu st. 10c LT-08105, Vilnius Lithuania

Tel +370 5 212 74 72 (Lithuania)
Tel +370 5 265 73 60 (International Calls Landline)
Tel +370 5 265 73 61 (Landline)
Fax +370 5 276 13 80
Email info@teltonika.lt
Web www.teltonika.lt